

# RIGID STEM DIAL THERMOMETERS TYPE TXR

TYPE	DRAWING	DIMENSIONS mm																																															
<p><b>A</b></p> <p>TXRxxxXA</p>		<table border="1"> <thead> <tr> <th rowspan="2">DIM.</th> <th colspan="5">CASE DIAMETER</th> </tr> <tr> <th>63</th> <th>80</th> <th>100</th> <th>160</th> <th>250</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>65</td> <td>83</td> <td>101</td> <td>161</td> <td>252</td> </tr> <tr> <td>B</td> <td>38</td> <td>37</td> <td>45</td> <td>45</td> <td>55</td> </tr> <tr> <td>C</td> <td>13</td> <td>13</td> <td>13</td> <td>13</td> <td>13</td> </tr> </tbody> </table>	DIM.	CASE DIAMETER					63	80	100	160	250	A	65	83	101	161	252	B	38	37	45	45	55	C	13	13	13	13	13																		
DIM.	CASE DIAMETER																																																
	63	80	100	160	250																																												
A	65	83	101	161	252																																												
B	38	37	45	45	55																																												
C	13	13	13	13	13																																												
<p><b>E</b></p> <p>TXRxxxXE</p>		<table border="1"> <thead> <tr> <th rowspan="2">DIM.</th> <th colspan="5">CASE DIAMETER</th> </tr> <tr> <th>63</th> <th>80</th> <th>100</th> <th>160</th> <th>250</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>65</td> <td>83</td> <td>101</td> <td>161</td> <td>252</td> </tr> <tr> <td>B</td> <td>38</td> <td>37</td> <td>45</td> <td>45</td> <td>55</td> </tr> </tbody> </table>	DIM.	CASE DIAMETER					63	80	100	160	250	A	65	83	101	161	252	B	38	37	45	45	55																								
DIM.	CASE DIAMETER																																																
	63	80	100	160	250																																												
A	65	83	101	161	252																																												
B	38	37	45	45	55																																												
<p><b>T</b></p> <p>TXRxxxXT-x</p>		<table border="1"> <thead> <tr> <th rowspan="2">DIM.</th> <th colspan="5">CASE DIAMETER</th> </tr> <tr> <th>63</th> <th>80</th> <th>100</th> <th>160</th> <th>250</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>65</td> <td>83</td> <td>101</td> <td>161</td> <td>252</td> </tr> <tr> <td>B</td> <td>38</td> <td>37</td> <td>45</td> <td>45</td> <td>55</td> </tr> <tr> <td>C</td> <td>13</td> <td>13</td> <td>13</td> <td>13</td> <td>13</td> </tr> </tbody> </table>	DIM.	CASE DIAMETER					63	80	100	160	250	A	65	83	101	161	252	B	38	37	45	45	55	C	13	13	13	13	13																		
DIM.	CASE DIAMETER																																																
	63	80	100	160	250																																												
A	65	83	101	161	252																																												
B	38	37	45	45	55																																												
C	13	13	13	13	13																																												
<p><b>F</b></p> <p>TXRxxxXF</p>		<table border="1"> <thead> <tr> <th rowspan="2">DIM.</th> <th colspan="5">CASE DIAMETER</th> </tr> <tr> <th>63</th> <th>80</th> <th>100</th> <th>160</th> <th>250</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>65</td> <td>83</td> <td>101</td> <td>161</td> <td>252</td> </tr> <tr> <td>B</td> <td>41</td> <td>40</td> <td>51</td> <td>51</td> <td>57</td> </tr> <tr> <td>D</td> <td>86</td> <td>110</td> <td>132</td> <td>196</td> <td>285</td> </tr> <tr> <td>F</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>2</td> </tr> <tr> <td>H</td> <td>3.5</td> <td>4</td> <td>5.5</td> <td>6</td> <td>6</td> </tr> <tr> <td>P</td> <td>75</td> <td>95</td> <td>116</td> <td>178</td> <td>270</td> </tr> </tbody> </table>	DIM.	CASE DIAMETER					63	80	100	160	250	A	65	83	101	161	252	B	41	40	51	51	57	D	86	110	132	196	285	F	5	5	5	5	2	H	3.5	4	5.5	6	6	P	75	95	116	178	270
DIM.	CASE DIAMETER																																																
	63	80	100	160	250																																												
A	65	83	101	161	252																																												
B	41	40	51	51	57																																												
D	86	110	132	196	285																																												
F	5	5	5	5	2																																												
H	3.5	4	5.5	6	6																																												
P	75	95	116	178	270																																												


# RIGID STEM DIAL THERMOMETERS

## Type TXR, with stainless steel case according to EN 13190

### STANDARD MODEL:

<b>CASE</b>	: bayonet lock, AISI304/1.4301, IP-65
<b>STEM - BULB</b>	: AISI321/1.4541, see page 8 - 11
<b>WINDOW</b>	: mineral glass 4 mm
<b>DIAL</b>	: aluminium, black figures on white
<b>POINTER</b>	: aluminium, black
<b>CONNECTION</b>	: see page 8 - 11
<b>RANGES</b>	: from -200 upto +800°C, see page 28 - 30

### EXAMPLE:



TXR100XA

<b>OVERLOAD</b>	: up to 30% F.S. (but max. 800°C)
<b>ACCURACY</b>	: ±1% F.S. / class 1
<b>MOVEMENT</b>	: brass
<b>OPTIONS</b>	: see page 32
<b>CONTACTS</b>	: see page 33-37
<b>PT-100</b>	: see page 42
<b>TRANSMITTER</b>	: see page 42

TYPE	MODEL	CASE DIAMETER (Ø in mm)				
		63	80	100	160	250
<b>A</b> 1130		TXR063XA	TXR080XA	TXR100XA	TXR160XA	TXR250XA
<b>E</b> 1131		TXR063XE	TXR080XE	TXR100XE	TXR160XE	TXR250XE
<b>T</b> 1133-x (x=A,B,C or D)		TXR063XT-x	TXR080XT-x	TXR100XT-x	TXR160XT-x	TXR250XT-x
<b>F</b> 1138		TXR063XF	TXR080XF	TXR100XF	TXR160XF	TXR250XF
<b>OPTION</b>		<b>EXTRA COSTS</b>				
<b>Lx</b>	<b>LIQUID FILLED CASE:</b> GLYCERINE (in combination with electrical device: Ondina oil, (see page 43))	TXR063Lx	TXR080Lx	TXR100Lx	TXR160Lx	TXR250Lx